

# FIRE EXTINGUISHING GROUPS

# **CTD**GROUP

CTD Group has been moving forward for more than 30 years with the same requirement: to learn, master and perfect its experiences, skills and the quality of its products. The group has become a key player in the maintenance of green spaces through garden cultivation, spraying, watering and dosing. It is also recognized in the world of firefighting for its dosing, transfer and high pressure equipment.

Fostering innovation and long-term vision, CTD Group is diversifying its activities and expanding its geographic reach from France to the international stage. CTD Group manages the activities of the companies CTD and YVMO. The head office is based in Guéreins, north of Lyons, FRANCE.





# **COMPANY STRENGHTS**



## CUSTOMER RELATIONSHIP

5 sales managers Supplying more than 60 countries Demonstration and training on site Tailor-made quotations



### R&D

Customised design 5% of the turnover in R&D 3D SolidWorks software Technical documentation customised



# QUALITY


ISO 9001 2015 Performance monitoring indicators Testing station UTAC approval



# AFTER SALES SEVICE

Helpline On-site intervention Equipment maintenance Spare Parts department

# SALES TERRITORIES | 3





EUROPE REST OF THE WORLD François CHEVERRY E-mail : fcheverry@ctdfrance.com Tel. : +33 (0)6 03 86 72 13



NORTH FRANCE BENELUX Vincent LEQUEUCHE E-mail : vlequeuche@ctdfrance.com Tel : +33 (0)6 34 35 91 24



SOUTH FRANCE FRENCH OVERSEAS TERRITORIES FRENCH SPEAKING AFRICAN COUNTRIES Fabrice CECILLON E-mail: fcecillon@ctdfrance.com Tel: +33 (0)6 48 43 75 68

Sales assistant Adeline DESPRES E-mail: adespres@ctdfrance.com Tel: +33 (0)4 74 06 47 01 Fax: +33 (0)4 74 06 47 09

# 4 | TRIOCEROS

Configuration




A

* Per default	THERMAL	ELECTRIC	HYDRAULIC
Pump type	Piston		
Pump flow	21 lpm	21 lpm	15 or 21 lpm
Pressure	200 bar	150 bar	200 bar
Dosing range	0.1 to 1%		
Power	Thermal (Diesel or Petrol)	Electric	Hydraulic
Length of hose*	25m hose		

**FEATURES** 

Possibility of supplying as a kit OR as a complete group on a frame with water and product tank



### **POSSIBLE OPTIONS**



Mud vacuum device



Isolation valve

25m hose extension

UUU 

Chest


40m reel

Tank filling hydro-injector



# TRIOCEROS | 5

A







# 6 | BP GROUPS



Α

#### **BP 250E BP 250D BP 300E** Type of pump Centrifugal Pump flow 250 lpm 250 lpm 300 lpm Pressure 6 bar 6 bar 8 bar Power Thermal Petrol Thermal Diesel Thermal Petrol Hose length 40m diam 1" Nozzle Variable spray and flow sure (Bar) Pressure (Bar) 5 Performance 2 250 300 Flow (lpm) Flow (lpm

**FEATURES** 

### REEL

Manual hose reel powered by the pump and equipped with 40 meters of semi-rigid Ø 1" hose crimped with GFR fittings.

# WATER TANK




**MOTOR PUMP** 

pressure gauge.

Centrifugal aluminum motor pump connected to the tank or to external suction comprising 1 DSP40 outlet, 2 DN25 outlets and equipped with a

Custom-made 12 mm HDPE tank adapted to the shape of the vehicle, equipped with an anti-balan Ball Baffle system, a vent, a visual tank level and a DSP40 filling



### NOZZLE

Nozzle cast in aluminum alloy, «cut teeth» diffusion head with variable flow and jet, opening by operating handle. 4 flow positions: 40/75/100/150 lpm at 6 bar

7.7

## FRAME

Custom-made aluminum profile frame with extension for loading by forklift truck and equipped with attachment points for Pickup skips.

# HP GROUPS | 7

### FEATURES

	HP 50E	HP 50D		
Type of pump	Piston Diaphragms	Piston Diaphragms		
Pump flow	0.4 to 50 lpm	0.4 to 50 lpm		
Pressure	40 bar	40 bar		
Power	Petrol	Diesel		
Hose length	40m diam 1/2"	40m diam 1/2"		
Nozzle	Full stream or spraying jet submachine gun	Full stream or spraying jet submachine gun		

Small 4WD SUV



Α

# powered

#### REEL

Hand-wound hose reel powered by the pump and equipped with 40 meters of flexible Ø  $1/2^{"}$  crimped hose.



Custom-made 12 mm HDPE tank adapted to the shape of the vehicle, equipped with an anti-balan Ball Baffle system, a vent, a visual tank level and a DSP40 filling.

WATER TANK



Piston / diaphragm motor pump connected to the tank including 2 u. 1/2" outlets and equipped with a pressure gauge

#### NOZZLE

Submachine gun type nozzle allowing a full stream or a spraying jet by means of an ergonomic handle.

### FRAME

Custom-made aluminum profile frame with extension for loading by forklift truck and equipped with attachment points for Pickup skips.







HEAD QUARTERS 11 rue de l'Industrie Parc d'entreprises Visionis - 01090 GUÉREINS FRANCE Tel: +33 (0)4 74 06 47 00 Fax: +33 (0)4 74 06 47 09 E-mail: info@ctdfrance.com www.ctdfrance.com

